



Use cases for smart lighting

In the project Smart Space, we identified needs from stakeholders to create use cases for smart lighting. A use case reflects a specific need (e.g. safe passage) in a specific area (e.g. during nightlife). In this way different use of smart lighting is detailed in a storyboard – a viable description of interactive use, including the related constraints and requirements.

Here we bring together all use cases as a repertoire of different opportunities to use smartness in interactive lighting.







Content

Use cases

•	MC1 - Atmosphere and light experience in shopping street de Lange Delft in Middelburg	5
•	MR1 - Safe cycling and walking crossings on through roads at the Rooseveltlaan Middelburg	16
•	OS1 - Atmosphere and light experience in the station square Oostende	20
•	OE2 - Lively urban space evoking (social) activities in the Victorialaan and the connections in Oostende	31
•	SN1 - Atmosphere and light experience in shopping street the Stationsstraat in Sint-Niklaas.	40
•	SN3 - Perceived safety at the night life area Sint-Nicolaasplein in Sint-Niklaas	55
•	TT2 - Supporting event experiences on Liberty Square and connecting roads in Thurles	72
•	TT1 - Safe cycling and walking along mixed traffic roads (R-roads) in Thurles	89








Smart Lighting is lighting that enables people to use and enjoy public space, by providing the right light at the right moment, the right place, and with the right atmosphere.

By integrating sensors and software controls into the system, street lighting can be automatically adjusted to the actual local needs, realizing both efficiency in light energy consumption and a higher level of well-being for people.




























Atmosphere and light experience in shopping street Lange Delft in Middelburg

Need

People indicate the need for a pleasant and comfortable street scene, where light is designed for pedestrians and cyclists and the bright and dark show windows are integral part of the atmosphere.

Use case

To make the historical city centre an attractive shopping area, where people stay longer and return, different routes are created for different target groups with different (lighting) experience. The light plan for the entire area needs to be designed integral and consists of 4 different scenarios.
















Scenario MC1.1 Passing-by safely and efficiently			
		Description	Providing good visibility and a pleasant atmosphere for people to pass-by safely and efficiently. With well-designed lighting scenes at low light levels and different scenes that dim further over the course of the evening and night.
		Timing	Always on
		People	All people
Use case		Activity	Passing-by
Use		Desired state of users	Safe and efficient
		Goal of the solution	Good functional lighting
		Function of lighting	Functional lighting level - light level as low as possible with sufficient homogeneity - adapted to seasons (flexibility)
		Function of 'smart'	n.a.
		Type of lights	General / public lighting (the basic lighting grid)
	D0	Scenes	Active: multiple dim scenarios with timer control
	Lighting	Light level	tbd
	_	Colour	(Tunable) white
stem		Adjacent streets/areas	Similar light levels
Requirements system		Activation of the scene	Timer control
iireme		Deactivation of the scene	Timer control
Requ		Dynamics within the scene	Dim scenarios over the evening and night - adjusted to other scenarios when needed
	Smart	Activation of the dynamics	Timer control
		Deactivation of dynamics	Timer control
		Data collection for system	n.a.









Scenario MC1.2 Providing identity and orientation				
		Description	Creating landmarks around the city centre to emphasize the historical identity and to provide orientation. With facade lighting on the monumental buildings in the city at the lowest possible level with sufficient contrast.	
		Timing	Seasonal scheme	
		People	All people	
Use case		Activity	Orientating	
Use		Desired state of users	Feeling at ease	
		Goal of the solution	Emphasize the monumental city	
		Function of lighting	Atmosphere creation through decorative facade lighting	
		Function of 'smart'	n.a.	
		Type of lights	Existing facade lighting (out of project scope)	
	bū	Scenes	Active: multiple dim scenarios with timer control	
	Lighting	Light level	tbd	
	=	Colour	Existing	
stem		Adjacent streets/areas	Not too bright to ensure desired contrast	
Requirements system		Activation of the scene	Timer and calendar control (integrated with other scenarios)	
ıireme		Deactivation of the scene	Timer and calendar control (integrated with other scenarios)	
Requ		Dynamics within the scene	Dim scenarios over the evening and night - adjusted to other scenarios when needed	
	Smart	Activation of the dynamics	Timer control	

Timer control

n.a.

n.a.

Deactivation of dynamics

Data collection for system

Creating an enhanced shopping experience by evoking people to explore the city and wander around less familiar areas. With multiple, specially-designed scenes that highlight the little gems and nice alleys in different routes that change









Presence and location of people

Data collection for system

Scenario MC1.4 Prolonging the stay

Providing an attractive and warm atmosphere on the squares to invite people to stay longer and have a drink or a bite. With a lighting scene that makes use of the features of the area in a layered lighting design, avoiding dark spots.









Presence and location of people

Data collection for system









Safe cycling and walking crossings on through roads at the Rooseveltlaan Middelburg

Need

People indicate that the main road needs to be not or much less lighted if safe crossings are created for intersecting traffic.

Use case


The storyboard of the interactive use consists of one scenarios that describes how good visibility of cyclists and pedestrians crossing the road is provided to increase their (perception of) safety. With multiple lighting scenes that dim further over the course of the evening and night, with constant contrast for a brightly illuminated crossing, a bicycle/footpath levelling up and down towards this intersection and a maximum dimmed or no lighting on the main road .





Scenario MR1.1 Crossing safely

Providing good visibility of cyclists and pedestrians crossing the road to increase their (perception of) safety. With multiple lighting scenes that dim further over the course of the evening and night, with constant contrast for a brightly illuminated crossing, a bicycle/footpath levelling up and down towards this intersection and a maximum dimmed or no lighting on the main road.









Scenario: Crossing safely				
		Description	Providing good visibility of cyclists and pedestrians crossing the road to increase their (perception of) safety. With multiple lighting scenes that dim further over the course of the evening and night, with constant contrast for a brightly illuminated crossing, a bicycle/footpath levelling up and down towards this intersection and a maximum dimmed or no lighting on the main road.	
		Timing	Every night - dusk till dawn	
		People	All people	
Use case		Activity	Cycling and walking / car driving	
Use		Desired state of users	Feeling safe when crossing the road (cyclists and pedestrians) and safe driving (motorised driving)	
		Goal of the solution	Enable maximum dimming on roads with separate lanes for motorised traffic by increasing the visibility of crossings for pedestrians and cyclists	
		Function of lighting	Making car drivers aware of potential cyclists or pedestrians crossing the road at specific places	
		Function of 'smart'	n.a.	
		Type of lights	General lighting	
		Scenes	Active: multiple dim scenarios with timer control	
	Lighting	Light level	As low as possible with sufficient contrast between the crossing, the bicycle/footpath and the main road. In built areas this means maximum dimmed and in unbuilt areas no lighting at all for the main road.	
	_	Colour	White	
tem		Adjacent streets/areas	Minimal light levels, ensuring sufficient contrast	
nts sys		Activation of the scene	Timer control	
Requirements system	Smart	Deactivation of the scene	Timer control	
Requ		Dynamics within the scene		
		Activation of the dynamics	n.a.	
		Deactivation of dynamics		
		Data collection for system	Initial measurement of the road use, to select the desired timeslots for dim scenarios	
		Data collection for learning	Number of road users (walking, cycling and driving) and their speed.	




















Atmosphere and light experience in the station square Oostende

Need

People indicate the need for an attractive, cosy place to be and to stay with a comfortable atmosphere. A place that welcomes visitors into the city.

Use case

The total storyboard of the interactive use consists of 4 scenarios that reflect different use by different target groups, related by routes varying over time and place.







Scenario OS1.1 Walking safely

Providing a good overview of the area to guide pedestrians (mainly neighbouring residents) to their destination safely and comfortable. With a well-designed, static lighting scene at low intensity.










Amount of people (presence and location), number of people tripling

Data collection for system











Scenario OS1.2 Commuting efficiently					
		Description	Providing a good overview of the area to avoid collision. With a well-designed, static lighting scene at low intensity that supports the flows of commuters (pedestrians, cyclists, bus and tram-passengers) to/fro train station.		
		Timing	Peak hours: weekdays between 6:30/sunrise and 8:30 Peak hours: weekdays between 16:00/sunset and 1		
		People	Cyclists, pedestrians, bus and tram passengers		
case		Activity	Catching the train, bus or tram	Returning	
Use		Desired state of users	Safe and efficient	Safe and efficient	
		Goal of the solution	Homogeneous lighting on the square		
		Function of lighting	Supporting large flows of people and providing good visibility.		
		Function of 'smart'	n.a.		
		Type of lights	Public lighting		
	bū	Scenes	Static lighting scene		
	Lighting	Light level	Minimum lighting le	evel with good visibility	
	7	Colour	Cool white		
stem		Adjacent streets/areas	Ensure low contrast (similar light levels)		
Requirements system		Activation of the scene	Timer control, calendar (working days)		
Jireme		Deactivation of the scene	Timer control		
Requ		Dynamics within the scene			
	Smart	Activation of the dynamics	n.a.		
		Deactivation of dynamics			
		Data collection for system		n.a.	
		Data collection for learning	Amount of people (presence and location), number of disturbances,	/people bumping into each other, perception of efficiency and comfort	

















Amount of people (presence and location), number of disturbances/people bumping into each other, perception of efficiency and comfort

Data collection for system













OE2.1 Interactive playing



OE2.2 Communal living room









Lively urban space evoking (social) activities at Victorialaan and the connection with

Central park at Sea in Oostend

Need

People indicate the need for a lively urban space where they can meet and do activities together. A space that evokes (social) activity and cohesion by evoking people to come and stay outside.

Use case

The total storyboard of the interactive use consists of 2 scenarios and reflect different use by different target groups. One aims for the walking facilities with water features in the Victoriastraat and one on the Central Park.















Scenario OE2.1 Interactive playing (1 of 2)

RGB

	Description	With specially-designed playful elements that interact with people, their movements and the environment (e.g. sun set experience or a good night kiss).						
	Timing	End afternoon & early even	ning from autumn to spring	Beautiful sunsets all year round		Every evening and morning (before 23:00 and after 6:00)	Every evening around 23:00	
	People	Children a	and elderly	Everybody		Everybody	Everybody	
case	Activity	Interactive playing		Doing something else		Strolling along	Doing something else	
Use	Desired state of users	Having fun		Enjoying the experience together		Comfortable	Enjoying the experience together	
	Goal of the solution	Evoke people to be physically and socially active		Drawing the people to a joint enhanced sunset experience		Comfortable and pleasant atmosphere	Drawing the people to a joint enhanced experience	
	Function of lighting	Enhanced atmosphere adapting to the situation with interactive lighting		Enhanced atmosphere		Contribute to the atmosphere	Light show as transition to the night scene	
	Function of 'smart'	Gaming element for different user groups at different times of the evening		Realtime sensing of 'quality' of the sunset and the colours		Real time reacting to light level	t.b.d.	
	Type of lights	Special lighting elements and/or projection	General public lighting	General public lighting	Special lighting elements	General public lighting	General public lighting	Special lighting elements
system	Scenes	Interactive: different play elements light up during use/playing	Static lighting scene	Interactive: adapting to the sunset in light level and colour		Interactive: light levels based on the weather conditions	Interactive: light show using the special lighting elements, with multiple lighting shows that are randomly displayed, with special experience on special days	
irements sy	Light level	Sufficiently bright to be clearly visible	Low level, to ensure clear visibility of the special lighting clearly	Gradient in light level towards the end of the street	Matching with the sunset itself	Pleasant at minimum level related to weather conditions at the walking lines, and highly dimmed at the road	Maximum dimmed (night scene)	t.b.d.

Creating a fun and lively area that evokes people to be active to walk, play or enjoy the sun set experience together.

RGB

dimmed at the road

(Tunable) white

Ensure low contrast (similar

lighting levels)

North-West Europe SMART-SPACE

Colour

Adjacent

streets/areas



Ensure low contrast (similar lighting levels - also dimming to

night scene)

(Tunable) white



RGB

Not too bright to ensure the visibility of the experience

- to be continued on next page -

(Tunable) white

Ensure low contrast (similar lighting levels)

(Tunable) white









Scenario OE2.1 Interactive playing (2 of 2)

		Activation of the scene	Timer control, from autumn to spring - starting with a trigger or demo		Triggered by sunset and assessment of the quality	Surrounding light level sensor (too dark)
		Deactivation of the scene	Timer control		End of sunset	Between 23:00 and 6:00
system		Dynamics within the scene	Multiple users can play a together or alone	n.a.	Matching the dynamics of the sunset in level and colour	Adaptive to surrounding light levels
nts	(0	Activation of the dynamics	Participation of people		Sensor or camera that analyses the sunset	Continuous measuring with surrounding light level sensor
Requireme		Deactivation of dynamics	End of participation		End of sunset	n.a.
		Data collection for system t.b.d. (depending on the interaction with the playing element)	Quality and colours of the sun set. Surrounding light levels. Weather conditions.	Surrounding light levels (and thresholds for on/off and dimming)		
		Data collection	Amount of people present	n.a.	Amount of people present, weather conditions, their appreciation of the experience (e.g.	Amount of people strolling along in different weather

through social media)



for learning














Scenario OE2.2 Communal living room				
		Description	Creating a pleasant and 'homey' atmosphere to invite residents and neighbouring residents to stay, relax and socialise together. With special designed lighting scenes that react to the presence of people and their activities, and invite others to join in.	
		Timing	Dinner time (after/at sunset)	
		People	Everybody, incl. residents from adjacent neighbourhoods	
Use case		Activity	Spending time together (e.g. in a handy craft market, or preparing food together)	
Use		Desired state of users	Having fun together	
		Goal of the solution	Drawing people together to spend time together	
		Function of lighting	Creating a pleasant and 'homey' atmosphere	
		Function of 'smart'	Detecting the presence of people and notify others through an app or message	
		Type of lights	Special lighting elements	
	b0	Scenes	Reacts on the presence of people and the activity they are doing	
	Lighting	Light level	Pleasant and cosy	
	_	Colour	t.b.d.	
stem		Adjacent streets/areas	Not too bright to ensure the visibility of the experience	
nts sy		Activation of the scene	Timer control	
Requirements system		Deactivation of the scene	Timer control	
Requ		Dynamics within the scene		
	Smart	Activation of the dynamics	n.a.	
		Deactivation of dynamics		
		Data collection for system	Presence of people, detecting type of activity	

Data collection for learning

Amount of people present, amount of people that install the app/subscribe for the notifications, amount of people that react to notifications, their appreciation of the experience








Use case SN1 Stationsstraat Sint-Niklaas













Atmosphere and light experience in shopping street the Stationsstraat in Sint-Niklaas

Need

People indicate the need a pleasant and cosy street scene, where light is designed for pedestrians and cyclists and the bright and dark shop windows are integral part of the atmosphere.


Use case

The total storyboard of the interactive use consists of 6 scenarios that reflect different use by different target groups, related by timing over the day and night. The aim is to dim the light as much as possible, while creating equality and a nice atmosphere.















Scenario SN1.1 Commuting safely on a temporary cycle lane Providing visibility of cyclists and separating flows in a shared space to reduce the number of accidents and conflicts. Description With a temporary light path for cyclists at the end of the afternoon on school days. **Timing** End of the afternoon on school days People Pupils Activity Cycling Desired state of users Safe and fast moving between pedestrians Goal of the solution Less accidents and conflicts between cyclists and pedestrians Function of lighting Clearly visible lane for cyclists Function of 'smart' n.a. Type of lights Public lighting and/or additional lights Scenes Static: light path for cyclists Lighting P2 Light level Sufficient contrast with environment Colour t.b.d. Requirements system Adjacent streets/areas n.a. Activation of the scene Timer control (end of school) & calendar (school days) Deactivation of the scene Timer control Dynamics within the scene Smart Activation of the dynamics n.a.

Initial measurement of amount and position of pedestrians and cyclists during afternoons on school days

Amount and position of pedestrians.

Amount and position of cyclists.

Deactivation of dynamics

Data collection for system









Scenario SN1.2 Playful interaction				
		Description	Creating a fun get-together setting where users can play and spend more time outside together. With an interactive lighting installation that enables users to create and display personal content real time.	
		Timing	End of the afternoon on school days	
		People	Pupils	
Use case		Activity	Lingering and chilling	
Use		Desired state of users	Having fun time together	
		Goal of the solution	Making people stay longer and contribute to a nice atmosphere and liveliness	
		Function of lighting	Projection of user content on wall or floor	
		Function of 'smart'	With the help of an app people can create content and project to the floor or a wall	
		Type of lights	Projector / beamer	
	bo	Scenes	Interactive: real time user content projection	
	Lighting	Light level	Sufficient contrast with environment	
	_	Colour	RGB projection	
stem		Adjacent streets/areas	Not too bright to reduce required light level of projection	
Requirements system		Activation of the scene	Timer control (end of school) & calendar (school days)	
iireme		Deactivation of the scene	Timer control	
Requ		Dynamics within the scene	Multiple users can project content after each other Multiple users can create content together - e.g. drawing	
	Smart	Activation of the dynamics	Smart phone app	
		Deactivation of dynamics	Timer and/or after 15 min. Inactivity	
		Data collection for system	n.a.	

Amount of people

Scenario SN1.3 Enhanced shopping experience

Creating a warm atmosphere and extra surprising experience to make people enjoy the environment and keep coming back. With multiple lighting scenes that light up different historical buildings, to refresh the experience regularly and keep it lively all year round.









Scenario SN1.3 Enhanced shopping experience				
		Description	Creating a warm atmosphere and extra surprising experience to make people enjoy the environment and keep coming back. With multiple lighting scenes that light up different historical buildings, to refresh the experience regularly and keep it lively all year round	
		Timing	Shopping hours & weekends	
		People	Shoppers & visitors	
Use case		Activity	Shopping / visiting	
Use		Desired state of users	Extra experience and service so people keep returning	
		Goal of the solution	Creating maximum and changing atmosphere with minimum energy	
		Function of lighting	Atmosphere creation through decorative facade lighting	
		Function of 'smart'	n.a.	
		Type of lights	Facade lighting	
	b 0	Scenes	Active: multiple scenes for facade lighting to keep it lively all year round, related to special events or activities (e.g. Huis van de Sint).	
	Lighting	Light level	Minimum to create a nice atmosphere	
	_	Colour	t.b.d.	
stem		Adjacent streets/areas	Ensure low contrast (similar lighting levels)	
Requirements system	Smart	Activation of the scene	Timer control & calendar (planned scenes)	
uireme		Deactivation of the scene	Timer control	
Requ		Dynamics within the scene		
		Activation of the dynamics	n.a.	
		Deactivation of dynamics		
		Data collection for system	n.a.	

Amount of people









Scenario SN1.4 Passing-by in a pleasant atmosphere and safely in the night Providing a pleasant atmosphere and a feeling of safety for people to pass-by. Description With well-designed lighting scenes at low light levels that dim further over the course of the evening and night, adapting the public lighting to the available (private) lighting in the area. Timing Always (when lighting is required) People Employees, residents and passers-by Activity Passing by (also through traffic to station), going home, walking the dog Desired state of users Feel safe and at ease Goal of the solution Creating a feeling of comfort and safety with minimum energy Function of lighting Lowest lighting level, very homogeneous, sufficient for police camera's Function of 'smart' n.a. Type of lights Public lighting Active: multiple scenes to adapt the public lighting to the available lighting (emitted by shop windows, facades, private lighting etc.) through Scenes regular measurements and agreements with shop and building owners to be able to dim as deep as possible. Lighting Light level Minimum to create a nice atmosphere Colour Tuneable white Requirements system Adjacent streets/areas Ensure low contrast (similar lighting levels) Activation of the scene Timer control & calendar (planned scenes) Deactivation of the scene Timer control Dynamics within the scene Smart Activation of the dynamics n.a.

Initial measurement of the surrounding lighting over the course of the evening (emitted by shop windows, facades, private lighting)

Amount of people

Deactivation of dynamics

Data collection for system









Scenario SN1.5 Enhanced night life experience					
		Description	Creating a surprising experience to make going out a memorable event, and tempt visitors to return. With a well-timed scene that lights-up objects in the street and creates a 'drawn-in/waving goodbye' experience for people going out.		
		Timing	Evenings on Wednesdays to Sundays		
		People	People going out		
Use case		Activity	Going out	Going home	
Use		Desired state of users	Nice atmosphere and safety on their way to the movies, concert, etc.	Nice atmosphere and safety on their way home	
		Goal of the solution	Making people feel welcome, drawing people into the street, so they stay longer	Waving people goodbye with a wink, so they return more often	
		Function of lighting	Dynamic attraction points through the street	Say goodbye to people heading home	
		Function of 'smart'	n.a.	n.a.	
		Type of lights	Public lighting and special lighting elements on facades or greenery	t.b.d.	
	bo	Scenes	Active: multiple scenes e.g. through special themes related to events (movies, concerts)	t.b.d.	
	Lighting	Light level	Minimum to create a nice atmosphere		
	_	Colour	t	.b.d.	
stem		Adjacent streets/areas	Ensure low contrast	t (similar lighting levels)	
Requirements system	Smart	Activation of the scene	Timer control & calendar	(planned scenes Wed - Sun)	
Jireme		Deactivation of the scene	Time	er control	
Requ		Dynamics within the scene			
		Activation of the dynamics	n.a.		
		Deactivation of dynamics			
		Data collection for system	Regular measurement (e.g. quarterly) of flows of people (incl. walking speed of lighting up	when entering or leaving the street) on nightlife evenings, to ensure right timing attraction points	
		Data collection for learning	Presence and I Appreciation	location of people. of the experience	









Scenario SN1.6 (Un)Loading and commuting safely				
		Description	Creating good visibility to avoid accidents between loading and unloading delivery vans and commuting cyclists and pedestrians. With a brighter area around parked vans, reacting to the presence of vans, to warn cyclists.	
		Timing	Early morning (working/schooldays)	
		People	Truck drivers & builders vs. pupils & commuters	
Use case		Activity	Loading / unloading vs. going to school /work	
Use		Desired state of users	Safe and efficient	
		Goal of the solution	Ensuring safety during (un)loading between commuting cyclists and pedestrians	
		Function of lighting	Bright area/spot	
		Function of 'smart'	Detecting presence and position of vans	
		Type of lights	Public lighting	
	bū	Scenes	Multiple lighting scenes (bright area on and off), reacting to the presence or absence of vans	
	Lighting	Light level	high (spot)	
	_	Colour	White	
stem		Adjacent streets/areas	Ensure low contrast (similar lighting levels)	
Requirements system		Activation of the scene	Timer control & presence of vans	
uireme		Deactivation of the scene	Absence of vans	
Requ		Dynamics within the scene		
	Smart	Activation of the dynamics	n.a.	
		Deactivation of dynamics		
		Data collection for system	Presence and position of parked vans	

Data collection for learning

Number and position of parked vans, duration of stay of parked vans








Use case SN3 Sint-Nicolaasplein Sint-Niklaas













Perceived safety at the night life area Sint-Nicolaasplein in Sint-Niklaas

Need

People indicate the need for a nice and safe night life atmosphere, where unwanted behaviour is avoided and surveillance is supported.


Use case

The total storyboard of the interactive use consists of 7 scenarios that reflect different use by different target groups, related by the position within the area.
















Scenario SN3.1 Protecting safety Ensuring safety on the entire square by a supporting the guards in their jobs with technology to detect and locate incidents and de-escalate aggressive behaviour, as well as lighting up available escape routes to enable smooth evacuation of the square in case of calamity. Description With an interactive system that reports the occurrence and location of incidents to the control room, reacts with controllable light spots and supports different evacuation routes in case of calamities. Timing On busy nights out People Control room police Activity Provide warning to rebels Detecting incidents and calamities Activate local security guards Activate evacuation Reliable incident detection (no false Desired state of users Safe and pleasant area De-escalation without intervention De-escalation with intervention alarms, no missed incidents) & fast and controlled evacuation Goal of the solution Creating safety in night time situations Creating safety in emergency situations Ensuring good visibility for camera's De-escalate by special scene or lighting up Create light corridors to indicate safe Function of lighting regardless of the lighting scenarios and the location of the incident with n.a. (sensing only) escape routes levels controllable light spot Function of 'smart' Detection of incidents and location(e.g. through 3D sound camera's) Type of lights General lighting & special lighting elements Infrared light and camera's General lighting Reactive: multiple lighting scenes (e.g. Interactive: different evacuation routes Scenes t.b.d. bright spot) based on location of calamity Lighting Light level High (spots) High (escape routes) n.a. Colour n.a. (infrared) White White, RGB Not too bright to reduce required light level Requirements system Adjacent streets/areas Ensure low contrast (similar lighting levels) of light spot Incident detection by system, activation by Incident detection by system, activation by Activation of the scene control room control room n.a. n.a. Deactivation of the scene Control room Control room Extra attention to available, safe escape Dynamics within the scene routes, guiding lights to exits of the square Smart Control room based on location of calamity Activation of the dynamics n.a. and progress of the evacuation Deactivation of dynamics Control room Data collection for system Incidents and location Calamity and location

Amount and location of incidents/calamities


















Presence and location of people.









Scenario SN3.4 Time to go home Creating a cool and unpleasant atmosphere to warn people subtly that the evening is ending and ensuring they will leave the square and avoid lingering around when the pubs Description are closed. With multiple lighting scenes to increase light levels when people linger around and deeply dim when they have left, reacting to the presence (or absence) of people. Timing Late evenings (Wed-Sun) People Visitors Activity Leaving Desired state of users Gentle ending of a nice evening and avoiding lingering around Goal of the solution Gentle warning that pubs will close soon, so people can leave the square smoothly Creating a less pleasant atmosphere to avoid people Dimming and switching off, to create a neutral Function of lighting Creating a light corridor to indicate exits in a subtle way lingering around after closing time atmosphere Function of 'smart' Presence and absence of people Type of lights Decorative lighting on north and south side General lighting General lighting & special lighting elements Static: highlighting the exits routes (same as evacuation Scenes Reactive: slowly increasing and dimming lighting levels Active: slowly dimming lighting levels of decorative lighting routes) Lighting Light level Off t.b.d. (medium - high) t.b.d. (medium - high) Colour Tuneable white White n.a. Requirements system Adjacent streets/areas Ensure low contrast (similar lighting levels) Activation of the scene Timer control & calendar (planned scenes related to event calendar?)

Timer control

Decreasing light levels from specific moment

Timer control

Timer or absence of people

Presence of people (when everybody left, the scenario can be turned off)

How much time is needed for all people to leave.

Increasing light levels from specific moment until all (?)

people have left, then go back to normal setting (deeply

dimmed)

Timer control (activating other scenario)

Increasing light levels from specific moment until all (?)

people have left, then go back to normal setting

(deeply dimmed)

Deactivation of the scene

Dynamics within the scene

Activation of the dynamics

Deactivation of dynamics

Data collection for system

Data collection for learning

Smart









Scenario SN3.5 (Un)Loading and parking bikes safely Providing a good overview of the area for people to use the bike parking safely and create good visibility for efficiently unloading of goods for the café's and restaurants -Description specifically at the north side. With a well-designed lighting scene at a low intensity, avoiding dark spots and create bright sport for parked vans or cars, when present. Timing On early mornings during weekdays Evenings (Wed-Sun) People Cyclists Tenants Activity Loading and unloading Park/fetch bicycle Desired state of users work efficient Feel safe and ensure bike is stalled safely Goal of the solution Good, functional lighting Good, functional lighting Function of lighting Functional lighting levels Homogeneous lighting to feel safe and enable social control Function of 'smart' Detection of vans/trucks n.a. Type of lights General lighting General lighting Scenes Highlighted (un)loading zone, reacting to the presence of vans/cars Static: homogeneous lighting of parking area Lighting Light level t.b.d. (medium - high) t.b.d. (low - medium) Colour White White Requirements system Adjacent streets/areas Ensure low contrast (similar lighting levels) n.a. Activation of the scene Timer control & calendar (to differentiate between days of the week) Timer control & calendar (planned scenes related to event calendar?) Deactivation of the scene Timer control Timer control Dynamics within the scene Highlighting the (un)loading zone Smart Activation of the dynamics Presence detection (detecting delivery vans specifically) n.a.

Timer or absence of vans

Presence of vans/cars

Presence and location of vans.

Duration of stay.

n.a.

Number of people.

Time of arrival/departure.

Deactivation of dynamics

Data collection for system










Scenario SN3.6 Inviting people to join Creating a welcoming entrance to the square in front of the church entrance to make people aware of the activities on Sint-Nicolaasplein and to invite them to take a look and Description enjoy themselves. With multiple lighting scenes that highlight the higher elements of the church facade (to be seen from the market place) and the side walls of the 'entrance'. changing according to the event or the season. Timing Afternoon/evening of days on which special events or activities are scheduled People Potentially interested people Activity Doing something else Arriving at the square Nice atmosphere and clear orientation on what is happening Desired state of users Discovering or experiencing something new left and right of the church Creating two equivalent but different routes left and right of Goal of the solution Drawing people from the Grote Market to the square through the main entrance the church Drawing attention and give a preview of the pleasant atmosphere on the square, and supporting equivalent routes Creating a different, easy understandable atmosphere on Function of lighting north and south side to the left and right Function of 'smart' n.a. Type of lights Façade lighting church - especially higher elements Projection on the side wall of the 'main entrance' Façade lighting church - especially lower elements Active: multiple lighting scenes based on activities (one Active: multiple lighting scenes based on activities (one scene Scenes t.b.d. per evening) per evening) Lighting Light level t.b.d. (medium) t.b.d. (medium - high) t.b.d. (medium) Colour White, RGB RGB projection White, RGB Requirements system Adjacent streets/areas Not too bright to reduce required light level of special lighting Timer control & calendar (planned scenes related to Timer control & calendar (planned scenes related to event Activation of the scene event calendar?) calendar?) t.b.d. Deactivation of the scene Timer control Timer control Dynamics within the scene Smart Activation of the dynamics t.b.d. n.a. n.a. Deactivation of dynamics Data collection for system t.b.d.

Presence and location of people, direction of people (north or south).









Scenario SN3.7 Passing-by safely					
		Description Ensuring a feeling of safety on the entire square for commuters and people passing-by at all times of the day and night. With good, functional lighting that ensures good visibility and highlights the commuting zone, reacting to the presence of people.			
		Timing	Early morning (everyday)	Night (everyday)	
		People	Commuters (on bike or foot)	Occasional cyclist or pedestrian	
case		Activity	Passing-by (specially at Apostelstraat)	Passing-by	
Use		Desired state of users	Safe and efficient	Safe	
		Goal of the solution	Good, functional lighting		
		Function of lighting	Functional lighting levels	Good visibility on route, homogeneity to create sense of safety	
		Function of 'smart'	n.a.	Presence detection to light up the route	
		Type of lights	General lighting		
	Lighting	Scenes	Static: highlighting the commuting zone at P4 level	Reactive: deeply dimmed, with 'highlighted' commuting zone based on presence	
		Light level	P4	P7 Minimal lighting level, with good visibility on axes (so the rest can be dimmed more)	
		Colour	White		
stem		Adjacent streets/areas	Ensure low contras	et (similar lighting levels)	
ents sy	Smart	Activation of the scene	Timer control & calendar (working days)	Timer control & calendar (to differentiate between days of the week)	
Requirements system		Deactivation of the scene	Timer control	Timer control (activating the early morning scenario)	
Req		Dynamics within the scene	n.a.	Highlighting the commuting zone	
		Activation of the dynamics		Presence detection	
		Deactivation of dynamics		Timer or absence of people	
		Data collection for system	n.a.	Presence of people	
		Data collection for learning	Amount and position of	people (walking and cycling)	

















Supporting event experiences on Liberty Square and connections in Thurles

Need

People indicate the opportunity to support local activities with adaptive, coloured lighting and connect these games, concerts, movies and parties better to the city centre to make it more lively.

Use case

The total storyboard of the interactive use consists of 7 scenarios that reflect different use by different target groups, related by timing over the day and night. The aim is to dim the light as much as possible, while creating a nice and fitting atmosphere.















Scenario TT2.1 Commuting safely Providing good visibility for the flows of commuters (schoolchildren arriving by car and bus, through-traffic and delivery drivers for shops and bars) to avoid Description accidents. With bright spots nudging people to use pedestrian crossings and pass safely with multiple lighting scenes adapting to different weather conditions. Timing Between 8:00 and 9:15 am and between 4:00 and 6:00 pm on schooldays People Children, parents dropping children off/picking them up, bus drivers, delivery truck drivers Activity Passing through or dropping off/picking up Desired state of users Safe and efficient Goal of the solution Avoiding accidents ("Keep the kids alive") Lighting to nudge people to use the official crossings and increase attention for **Function of lighting** Good functional lighting on the road and footpath pedestrians Function of 'smart' n.a. Type of lights Public lighting directed to the road and footpath Additional lighting for pedestrian crossings (playful?) Scenes Active with multiple scenes ensuring good lighting adapted to all weather conditions Lighting Light level Bright lighting level Very bright to ensure visibility in bright lighting levels Colour White tbd Requirements system Adjacent streets/areas Ensure low contrast (similar lighting levels) Activation of the scene Timer control & calendar (school days) in dark periods All day - all year Deactivation of the scene Sunrise Dynamics within the scene Smart Activation of the dynamics n.a. Deactivation of dynamics

Finding a way to assess the visibility in different weather conditions (e.g. fog sensors, low sunlight)

Amount of people, flow/routes (where they cross), the number of (near) accidents

Data collection for system









Scenario T	T2.2 En	hanced shopping experience	
		Description	Creating a warm atmosphere to attract more people in the afternoon and keep them longer in the area. With an uniform horizontal lighting scene at low intensity to emphasise the lighting of the shops and facades.
		Timing	Sunset to 6:00 pm (every day)
		People	Shoppers
Use case		Activity	Shopping and enjoying the centre
Use		Desired state of users	Extra experience to compete with online shopping
		Goal of the solution	Creating an attractive atmosphere that makes people stay longer
		Function of lighting	Creating a warm atmosphere at the footpath
		Function of 'smart'	n.a.
		Type of lights	Public lighting directed to footpath
	b 0	Scenes	Static
	Lighting	Light level	Adapt the public lighting to the available lighting (emitted by shop windows and façade lighting)
	_	Colour	tbd
stem		Adjacent streets/areas	Ensure low contrast (similar lighting levels), and public lighting directed to the road not too bright.
Requirements system		Activation of the scene	Light sensor (sunset)
iireme		Deactivation of the scene	Timer control
Requ	Smart	Dynamics within the scene	
		Activation of the dynamics	n.a.
		Deactivation of dynamics	

Light levels of the shop windows and facades

Amount of people

Data collection for system









Scenario	ГТ2.3 Ра	ssing-by safely			
		Description	Providing a good overview of the area to let people pass-by safely. With a well-designed, static lighting scene at low intensity.		
		Timing	Every day from 6:00 pm (or sunset if that is later) to sunrise, unless other scenarios are active		
		People	Everybody		
Use case		Activity	Passing-by		
Use		Desired state of users	Safe		
		Goal of the solution	Good functional lighting		
		Function of lighting	Creating good visibility with minimum light levels		
		Function of 'smart'	n.a.		
		Type of lights	All public lighting		
	D0	Scenes	Static		
	Lighting	Light level	Minimum lighting level with high homogeneity		
	_	Colour	(Cool) White		
stem		Adjacent streets/areas	Ensure low contrast (similar lighting levels)		
Requirements system		Activation of the scene	Timer control		
iireme		Deactivation of the scene	Timer control		
Requ		Dynamics within the scene			
	Smart	Activation of the dynamics	n.a.		
		Deactivation of dynamics			
		Data collection for system	n.a.		

Data collection for learning

Amount of people










Scenario 1	T2.4 Pro	Providing identity and orientation		
		Description	Creating landmarks around the city to emphasize the Thurles identity and to provide orientation. With facade lighting on the castles at the lowest possible level with sufficient contrast.	
		Timing	Sunset to 10:00 pm (every day)	
		People	Everybody	
case		Activity	Orientating	
Use case		Desired state of users	Enhanced experience	
		Goal of the solution Creating enhanced atmosph	Creating enhanced atmosphere and orientation means for residents and visitors	
		Function of lighting	Facade lighting on castles to create a pleasant atmosphere and provide identity	
		Function of 'smart'	n.a.	
		Type of lights	Facade lighting (out of project scope)	
	b0	Scenes	Active: multiple scenes to dim during evening and night and to adapt to seasons	
	Lighting	Light level	Sufficient but as low as possible	
		Colour	tbd	
tem		Adjacent streets/areas	Dimmed to be able to see the landmarks lighting up	
Requirements system		Activation of the scene	Timer control (& calendar days for seasonal effects?)	
iireme		Deactivation of the scene	Timer control	
Requ	Smart	Dynamics within the scene		
		Activation of the dynamics	n.a.	
		Deactivation of dynamics		

n.a.

n.a.

Data collection for system









Scenario TT2.5 Enhanced nightlife experience Creating a pleasant atmosphere during pub hours to make the area lively and enhance the safety of pedestrians, e.g. while moving between places, being Description picked up or grabbing a cab. With multiple lighting scenes that change over the night reacting to the private lighting and ensure overall low light levels to be able to create slighting brighter pick up points for people heading home. Thursdays to Sundays 8:00 pm to midnight Timing People Everybody Going to the pubs Activity Desired state of users Extra experience and safety for people heading home Creating an attractive atmosphere and safe area to walk around Goal of the solution Function of lighting Creating a warm atmosphere at the footpath and terraces and create a slightly brighter pick-up point for people heading home. Adapt the public lighting to the available lighting (emitted by pubs and Function of 'smart' n.a. facades) Type of lights General public lighting directed to footpath Additional decorative lighting (e.g. trees, terraces) Active with multiple scenes and multiple areas Scenes Lighting Adjusted to the private lighting to create an overall pleasant atmosphere, but not too bright to reduce the required lighting level of decorative lighting tbd Light level and pick-up 'spots' Colour tbd Requirements system Adjacent streets/areas Dimmed to emphasize the footpath as brightest area, also lights directed to the road are dimmed Activation of the scene Timer control, calendar Deactivation of the scene Timer control

Adjusting to changing light emitted by pubs (to balance light levels of public and private lighting)

tbd (e.g. timer control when agreed with pub owners or light sensor for automatic adjustment)

tbd

Light levels of the pubs and facades

Amount of people

Smart

Dynamics within the scene

Activation of the dynamics

Deactivation of dynamics

Data collection for system









Scenario	TT2.6 Ch	ristmas experience	
		Description	Creating a fabulous Christmas experience with multiple scenes to change over time to keep it interesting for the entire Christmas season
		Timing	1 Dec - 15 Jan between 3:00 pm and 2:00 am
		People	Everybody
case		Activity	Passing-by or staying in the area
Use case		Desired state of users	Exited
		Goal of the solution	Creating an enhanced atmosphere
		Function of lighting	Creating a special Christmas feeling
		Function of 'smart'	n.a.
		Type of lights	Projection or special lighting elements
	D0	Scenes	Active with multiple scenes (e.g. one per evening) to keep it interesting for a longer period
	Lighting	Light level	Bright to emphasize the effect
	_	Colour	RGB
stem		Adjacent streets/areas	Dimmed to emphasize the special lights
Requirements system		Activation of the scene	Timer control, calendar
ireme		Deactivation of the scene	Timer control
Requ	ť	Dynamics within the scene	
		Activation of the dynamics	n.a.
		Deactivation of dynamics	
		Data collection for system	n.a.

Appreciation of the different scenes, amount of visitors
















Use case TT1 R498 & R660 Thurles, Tipperary













Safe cycling and walking along mixed trafic roads R498 and R660 in Thurles

Need

People indicate the need for safe cycling and walking along the mixed traffic roads, where the lighting should be aimed at pedestrians, to identify and highlight them and to warn and nudge the car drivers on the main road.

Use case

The storyboard of the interactive use consists of 2 scenarios. One aiming for the safety while walking and cycling along the road, the other enhancing the experience of being active at night at the Jimmy Doyle Loop.





Scenario TT1.1 Enhancing outdoor activities

Creating a fun and interactive area to make it attractive for all residents, including families with children, disabled and people with impaired vision to spend time outside and be physically active. With specially-designed lighting scenes and playful elements that interact with people and their activities to enhance their experience of e.g. strolling, cycling, jogging or dog walking.









Scenario TT1.1 Enhancing outdoor activities (1 of 2)

		Description	Creating a fun and interactive area to make it attractive for all residents, including families with children, disabled and people with impaired vision to spend time outside and be physically With specially-designed lighting scenes and playful elements that interact with people and their activities to enhance their experience of e.g. strolling, cycling, jogging or dog walking						
		Timing	Always	6:00pm-10:00pm	6:00pm-8:00pm	Events in the evening	Early morning	Dusk till early morning	
		People	Athletes & disabled	Residents - incl. families with kids and disabled		Visitors	Everybody		
case		Activity	Running / training / wheelchair exercise	Strolling	Interactive play	Visiting event in the stadium (e.g. Hurley matches or concerts)	Mixed use		
Use c		Desired state of users	Improve performance	Having fun		Comfortable and safe			
		Goal of the solution	Evoke people to be active outside and improve their performance	Evoke people to be physically accontent and gan		Creating a matching atmosphere related to the event	Good functional lighting	Create a warm and pleasant atmosphere with low light levels	
		Function of lighting	Enabling a better training with interactive lighting	Enhanced atmosphere with (i	interactive) lighting elements	Making visitors feel welcome	Functional lighting levels for safe commuting	Contribute to the atmosphere	
		Function of 'smart'	Gaming element for individual athletes	tbd (e.g. additional sound effects for visually impaired)	Gaming elements for kids	n.a.	n.	a.	
		Type of lights	Special lighting element	Projection	Special lighting element and/or projection	Projection and/or special lighting elements	General pu	blic lighting	
system	bū	Scenes	Interactive with multiple users	Active: multiple scenes that are changing over time, to keep it interesting	tbd, changing over time to keep it interesting	Active: multiple scenes related to the events	Active: with multiple scenes		
Requirements system	Lighting	Light level	Sufficiently bright to be clearly visible (also during the daylight?)			Normal light level	Low levels to ensure clear visibility of special lighting		
Requir		Colour	RGB	tbd	tbd	tbd	White (cool?)	White (warm?)	

n.a.

- to be continued on next page -

n.a.



Adjacent streets/areas



n.a.



n.a.

n.a.

Low levels to ensure clear

visibility of special lighting

Scenario TT1.1 Enhancing outdoor activities

Creating a fun and interactive area to make it attractive for all residents, including families with children, disabled and people with impaired vision to spend time outside and be physically active. With specially-designed lighting scenes and playful elements that interact with people and their activities to enhance their experience of e.g. strolling, cycling, jogging or dog walking.









Scenario TT1.1 Enhancing outdoor activities (2 of 2)

tbd

tbd

Multiple users can run together

Position, speed, direction, user

identity, user performance

profile Amount of people that install

the app, amount of users,

frequency of use, user

satisfaction

Activation of the scene

Deactivation of the scene

Data collection for system

Data collection for learning

Requirements system

Dynamics within the scene	or alone to improve their performance (e.g. against a virtual performance pacer)		tbd	the winning team)
Activation of the dynamics	Activation by a user (e.g. n.a. through a smart phone app)	n.a.	tbd	tbd
Deactivation of dynamics	Logging of by the user		tbd	tbd

Amount of people strolling

along during the year

Timer control

Timer control

tbd (depending on the interaction with the playing element)

Amount of children using it, the

frequency of use, user

satisfaction

Timer control & event calendar

Timer control & event calendar

tbd

Amount of people passing,

appreciation of the experience

Timer control - every day

Dawn sensor

n.a.

Dusk sensor

Timer control

Dim scenarios over evening and

night

Timer control

Timer control

Initial measurement of the road use, to select the desired

timeslots for dim scenarios

Amount of people present, perception of comfort















Scenario TT1.2 Safe walking & cycling along the road Providing good visibility of cyclists and pedestrians alongside the mixed traffic road to increase their safety. Description With local adaption of the lighting to create brighter areas around pedestrians and cyclists. Timing Dusk till xx pm and yy am till dawn xx pm till yy am People All road users Activity Walking and cycling commuters and schoolchildren Desired state of users Feeling safe Goal of the solution Enable maximum dimming on roads with mixed traffic by increasing the visibility of pedestrians and cyclists Function of lighting Making car drivers aware of cyclists and pedestrians alongside the road Function of 'smart' Detecting and highlighting presence of cyclists and pedestrians n.a. Type of lights Public lighting Scenes Active: with multiple scenes Interactive Lighting Light level Normal Colour White Adjacent streets/areas n.a. Activation of the scene Timer control - every day

Multiple scenes to dim during evening and night

Timer control

Timer control

Initial measurement of the road use, to select the desired timeslots for dim

scenarios

Timer control - every day

Number of cars, their speed and the number of accidents.

Perception of safety and comfort of cyclists and pedestrians.

Highlighting the area around pedestrians and cyclists

Presence of cyclists or pedestrians

Absence of cyclists of pedestrians

Presence, speed and direction of cyclists or pedestrians.

Number of false detections (outside the system)

Requirements system

Deactivation of the scene

Dynamics within the scene

Activation of the dynamics

Deactivation of dynamics

Data collection for system

Data collection for learning

Smart